



AS/ (CL) Commmands

User's Guide

Version: 1
Update: November, 2004

PPS – This command opens the main menu of Papirus' Word module. It is located under the library QGPL and does not require any parameters.

PPE - This command opens the main menu of Papirus' Excel module. It is located under the library QGPL and does not require any parameters.

PPM - This command opens the main menu of Papirus' Outlook module. It is located under the library QGPL and does not require any parameters.

PPN - This command opens the Administrator menu of Papirus' Word module. It is located under the library PPIRUS and does not require any parameters.

PPUSERLOG - This command opens the private events log of the current user. It is located under the library PPIRUS and does not require any parameters.

PPIRUS/PPADRSBOOK – This command opens the address book. It is located under the library PPIRUS and does not require any parameters.

PPSNDSP - This command sends a spool file via MS-Word to various destinations. It is located under the library QGPL and requires the following parameters:

Parameter	Description	Acceptable Values
Spoolf*	Name of the spool file.	Spool name.
Jobname*	Name of the job containing the spool file.	Name of the job, including user name and job number. * for the current job.
User	Name of the user activating the job. Required only if a name was enter in the parameter jobname.	User name.
Number	Number of the job. Required only if a name was enter in the parameter jobname.	000000 to 999999
Spoolnbr*	Number of the spool in the job.	0000 to 9999 *LAST for the most recently created spool.

Designid*	Name of the design (formatting definitions) with which the spool is sent to MS-Word.	Design name *USERDATA – name of the design is determined according to the name of the spool's userdata. *AS-IS – default design determined according to the width of the spool. *FILE - name of the design is determined according to the spool's file name.
savef	Whether to save the output document in DOC format.	*NO – don't save the output document *YES – save the output document
pcfilename	Name of the output document created by Papirus. Document is saved only when the parameter savef is set to *YES.	Desired document name.
Path	The path on the PC in which to save the output document.	Valid path for the Papirus PC server
Filetype	Type of the output document.	Currently not in use.
Printdoc	Whether to print the output document.	*NO – don't print the output document *YES – print the output document
Printnam	Name of the PC printer with which to print the output document. If kept blank, the default printer is used.	Name of the printer as was defined in Papirus' PC component.
CRTZIP	Creat Zip file	*NO – don't creat Zip file *YES – creat a Zip file
ZIPFPASS	Zip file password	Zip file password
Sendemail	Whether to send the output document by email. The document is sent as an email attachment.	*NO – don't send the output document by email *YES – send the output document by email
Emailsbj	Subject of the email sent by Papirus.	Desired email subject.

Emailto	Email TO destination address. At least one email address is required if the parameter sendemail was set to *YES.	Up to 20 email addresses can be entered by using +.
Emailcc	Email CC destination address.	Up to 20 email addresses can be entered by using +.
Emailsender	Email address of the sender.	Valid email address of the SMTP server.
Attachtitl	Email attachment name.	Desired name for the email attachment.
Attachtype	Email attachment format.	D – doc, H – html, T – txt, G – gif, P – pdf
Sendfax	Whether to send the output document by fax.	*NO – don't send the output document by fax *YES – send the output document by fax
Faxsbj	Subject of the fax sent by Papirus.	Desired fax subject.
Faxnbr	Fax destination number. At least one fax number is required if the parameter sendfax was set to *YES.	Up to 20 fax numbers can be entered by using +.
Sendsms	Whether to send a SMS message while producing the output document.	*NO – don't send SMS *YES – send SMS
Smsmessage	Text of SMS message.	Desired text.
Smsnbr	SMS destination number. At least one SMS number is required if the parameter sendsms was set to *YES.	Up to 20 cellular phones' numbers can be entered by using +.
Sndfreetxt	Whether to add free text to the email sent by Papirus.	*NO – don't add free text *YES – add free text
Freetext	Email message text.	Up to 10 lines of text can be added by using +.

* Required parameters

PPESNDSPL - This command sends a spool file via MS-Excel to various destinations. It is located under the library QGPL and requires the following parameters:

Parameter	Description	Acceptable Values
Spoolf*	Name of the spool file.	Spool name.
Jobname*	Name of the job containing the spool file.	Name of the job, including user name and job number * for the current job.
User	Name of the user activating the job. Required only if a name was enter in the parameter jobname.	User name.
Number	Number of the job. Required only if a name was enter in the parameter jobname.	000000 to 999999
Spoolnbr*	Number of the spool in the job.	0000 to 9999 *LAST for the most recently created spool.
Designid*	Name of the design (formatting definitions) with which the spool is sent to MS-Excel.	Design name *USERDATA – name of the design is determined according to the name of the spool's userdata. *FILE - name of the design is determined according to the spool's file name.
savef	Whether to save the output file in XLS format.	*NO – don't save the output file *YES – save the output file
pcfilename	Name of the output spread sheet created by Papyrus. Spread sheet is saved only when the parameter savef is set to *YES.	Desired spread sheet name.
Path	The path on the PC in which to save the output spread sheet.	
CRTZIP	Creat Zip file	*NO – don't creat Zip file *YES – creat a Zip file

ZIPFPASS	Zip file password	Zip file password
Sendemail	Whether to send the output spread sheet by email. The spread sheet is sent as an email attachment.	*NO – don't send the output spread sheet by email *YES – send the output spread sheet by email
Emailsbj	Subject of the email sent by Papyrus.	Desired email subject.
Emailto	Email TO destination address. At least one email address is required if the parameter sendemail was set to *YES.	Up to 20 email addresses can be entered by using +.
Emailcc	Email CC destination address	Up to 20 email addresses can be entered by using +.
Emailsender	Email address of the sender.	Valid email address of the SMTP server.
Attachtitl	Email attachment name.	Desired document name.
Sndfreetxt	Whether to add free text to the email sent by Papyrus.	*NO – don't add free text *YES – add free text
Freetext	Email message text.	Up to 10 lines of text can be added by using +.

* Required parameters

PPSNDSMS - This command sends a SMS message to cellular phones. It is located under the library PPIRUS and requires the following parameters:

Parameter	Description	Acceptable Values
Smsnum	SMS destination number.	Up to 20 cellular phones' numbers can be entered by using +.
Smsmsg	Text of SMS message.	Desired text.

PPSNDFILE - This command sends a data-base file to the PC to various destinations. It is located under the library QGPL and requires the following parameters:

Parameter	Description	Acceptable Values
Filename*	Name of the data-base file.	File name.

Libnam	Name of the library where the file is locate	Name of the library *libl is acceptable.
Design*	Name of the design (with field to send to the PC file).	Design name *ALL – all field are include.
Filetype*	PC file type	*txt – dos txt file. *xls – MS-EXCEL file. *ansi – windows txt file. *html – HTML file. *csv – csv file *txt2 – txt file
savef	Whether to save the output file in the PC.	*NO – don't save the output file *YES – save the output file
pcfilename	Name of the output PC file creat by the Papirus, file is saved only when the parameter savef is set to *YES.	Desired spread sheet name.
Path	The path on the PC in which to save the output file.	
CRTZIP	Creat Zip file	*NO – don't creat Zip file *YES – creat a Zip file
ZIPFPASS	Zip file password	Zip file password
Sendemail	Whether to send the output file by email. The file is sent as an email attachment.	*NO – don't send the output file by email *YES – send the output file by email
Emailsbj	Subject of the email sent by Papirus.	Desired email subject.
Emailto	Email TO destination address. At least one email address is required if the parameter sendemail was set to *YES.	Up to 20 email addresses can be entered by using +.
Emailcc	Email CC destination address	Up to 20 email addresses can be entered by using +.
Emailsender	Email address of the sender.	Valid email address of the SMTP server.
Attachtitl	Email attachment name.	Desired document name.
Sndfreetxt	Whether to add free text to the email sent by	*NO – don't add free text

	Papirus.	*YES – add free text
Freetext	Email message text.	Up to 10 lines of text can be added by using +.

* Required parameters

PPSNDTXT - This command sends text to the PC , various destinations and to any printer. It is located under the library PPIRUS and requires the following parameters:

Parameter	Description	Acceptable Values
savefile	Whether to save the output text in the PC.	*NO – don't save the output file *YES – save the output file
Sendemail	Whether to send the text by email.	*NO – don't send the text by email *YES – send the text by email
Sendfax	Whether to send the text by fax.	*NO – don't send the output document by fax *YES – send the output document by fax
Printdoc	Whether to print the output text.	*NO – don't print the output text *YES – print the output text
Freetext	message text.	Up to 50 lines of text can be added by using +.
pcfilename	Name of the output PC doc. created by the Papirus. doc. is saved only when the parameter savefile is set to *YES.	Require doc. name.
Path	The path on the PC in which to save the output doc.	
Printnam	Name of the PC printer which print the output document. If kept blank, the default printer is used.	Name of the printer as was defined in Papirus' PC component.
Emailsbj	Subject of the email sent by Papirus.	Require email subject.

Emailto	Email TO destination address. At least one email address is required if the parameter sendemail was set to *YES.	Up to 20 email addresses can be entered by using +.
Emailcc	Email CC destination address	Up to 20 email addresses can be entered by using +.
Emailsender	Email address of the sender.	Valid email address of the SMTP server.
Faxsbj	Subject of the fax sent by Papyrus.	Require fax subject.
Faxnbr	Fax destination number. At least one fax number is required if the parameter sendfax was set to *YES.	Up to 20 fax numbers can be entered by using +.

PPSNDWORD - This command sends document which already exist on the PC and sends it to varied destinations. located under the library PPIRUS and requires the following parameters:

Parameter	Description	Acceptable Values
Filename*	Name of the PC document.	File name.
Path	Name of the library where the document is located	
Sendemail	Whether to send the output file by email. The file is sent as an email attachment.	*NO – don't send the output file by email *YES – send the output file by email
Sendfax	Whether to send the output document by fax.	*NO – don't send the output document by fax *YES – send the output document by fax
Sndfreetxt	Whether to add free text to the email	*NO – don't add free text *YES – add free text
Emailsbj	Subject of the email sent by Papyrus.	Require email subject.
Emailto	Email TO destination address. At least one email address is required if the parameter	Up to 20 email addresses can be entered by using +.

	sendemail was set to *YES.	
Emailcc	Email CC destination address	Up to 20 email addresses can be entered by using +.
Emailsender	Email address of the sender.	Valid email address of the SMTP server.
Attachtitl	Email attachment name.	require name for the email attachment.
Attachtype	Email attachment format.	D – doc, H – html, T – txt, G – gif, P – pdf
Faxsbj	Subject of the fax sent by Papirus.	Require fax subject.
Faxnbr	Fax destination number. At least one fax number is required if the parameter sendfax was set to *YES.	Up to 20 fax numbers can be entered by using +.
Freetext	Email message text.	Up to 10 lines of text can be added by using +.

* Required parameters